



CAT6 RJ45 Keystone Jack with Dust Shutter 90° | 10 Pack White

Product Images



Description

CAT6 RJ45 Keystone Jack with Dust Shutter 90° | 10 Pack White

Compatible with keystone faceplates, surface mount boxes and patch panels*. Can be used with Australian HPM and CLIPSAL plates with the use of a bezel. Unique patented removable dust caps are handy to protect your outlets when not in use.

*Due to the proximity of each port on a patch panel, if you try and use these jacks for the majority of the ports you may come across an issue of not being able to physically fit them all in.

FEATURES

- Dual T568A and T568B Wiring
- RJ45 Complies with FCC Part 68 Standard
- 110/ Krone dual IDC connector compatible
- Provides termination for 22-26 AWG Wire
- Jack insertion life > 750 mating cycles
- IDC insertion life > 250 mating cycles
- Operating temperature -40 to + 60°C
- Unique patented removable dust caps to protect it from dust when not in use

SPECIFICATIONS

- CAT6
- Unshielded
- **Colour:** White
- **Qty in Pack:** 10
- **Gold-Plating:** 1.27um/50u inch
- **IDC insertion life:** > 250 mating cycles
- **Jack insertion life:** > 750 mating cycles
- **Operating temperature:** -40 to + 60 degrees Celsius
- **Contact:** 0.46mm Diameter Phosphor Bronze Gold Plated over Nickel
- **Dielectric withstanding voltage:** 1000v
- **Insulation Resistance:** 500m Ohm
- **Contact resistance:** 20m Ohm
- **DC resistance:** Max 0.1 Ohm
- **DC Current rating:** 1.5Amps

WARRANTY

3-years limited warranty

