



3m SC-ST OM4 Multimode Fibre Optic Cable | Salmon Pink

Product Images



Description

**m SC-ST OM4 Multimode Fibre Optic Cable | Salmon Pink

Fibre patch cables are thin, flexible fibres of glass that carry data, telephone conversations and emails high speed all over the world in a matter of seconds with much less interference than copper patch lead. Fibre Optic cables need less amplification to boost signals so they travel better over longer distances.

4Cabling's OM4 laser optimised multimode fibre optic patch leads are immune to EMI/ RFI frequency, The multimode optical fibre cables are manufactured using LSZH cables which conform to IEC, EIA TIA and Telcordia standards, ensuring minimal toxic gas emission in the event of a fire, this is often a requirement for many data centres and critical area applications. LSZH (Low Smoke Zero Halogen) sometimes referred to as LSOH is the material of choice for a green installation for the environmentally-conscious consumer.

4Cabling Multimode Fibre Optics leads provide a cost-effective solution for your cabling requirements.

OM4 is backwards compatible with OM3 Fibre optic.

FEATURES

- 4Cabling OM4 fibre patch leads conform to ISO/IEC 11801 & to ITU-T G.651.1, TIA/EIA 492AAAC and 492AAAD
- Individually labelled for lead tracing
- Low smoke zero halogen (LSZH) cable
- Manufactured with stringent quality control
- 100% optically tested for insertion loss to guarantee high quality&
- All leads are supplied with a factory test report
- Machine UPC (Ultra Physical Contact) connector
- All ends are polished and individually inspected for correct polishing
- Supports high-speed multi-channel data, voice & video applications
- Supports up to 100Gb transfer speeds
- UL approved fibre optic cables
- OM4 thickness 50 / 125µm (Core/Outside Cladding) Multimode (backwards compatible with OM3)

SPECIFICATIONS

- **Mode:** OM4 Multimode (backwards compatible with OM3)
- **Fibre Termination:** SC-ST
- **Duplex:** Salmon pink jacket zip cord
- **Length:** 3m
- **Colour:** Salmon Pink
- **Oversleeving:** 2mm

WHAT IS THE DIFFERENCE BETWEEN OM3 AND OM4 FIBRE NETWORK?

- Termination of the connectors are the same
- Transceivers are the same (both operate 850nm VCSELS (Vertical-Cavity Surface-Emitting Lasers))
- The same core size of 50/125µm
- Both fibres are Laser Optimised Multimode Fibre (LOMMF)
- OM4 is backwards compatible with OM3

The difference is the construction of the fibre cable, in that OM4 cable has better attenuation and can operate at a higher bandwidth than OM3 (4700MHz versus 2500). This means OM4 can transmit more data within the same distance.

The below illustration will highlight the main differences between fibre modes:

	Core/Cladding Diameter (µm)	Fast Ethernet 100BASEFX	1 Gigabit 1000BASE-SX	1 Gigabit 1000BASE-LX	10 Gigabit 10GBASE	40 Gigabit 40GBASE	100 Gigabit 100GBASE
Multimode							
OM1	62.5/125	2000 Meters	275 Meters	550 Meters	33 Meters	N/A	
OM2	50/125		550 Meters		82 Meters		
OM3*					300 Meters	100 Meters	100 Meters
OM4*					400 Meters	150 Meters	150 Meters
Singlemode							
OS1	9/125	2000 Meters	5 km at 1310nm	5 km at 1310nm	10 km at 1310nm		
* Laser Optimised							

	Core/Cladding Diameter (µm)	Fast Ethernet 100BASEFX	1 Gigabit 1000BASE-SX	1 Gigabit 1000BASE-LX	10 Gigabit 10GBASE	40 Gigabit 40GBASE	100 Gigabit 100GBASE
Multimode							
OM1	62.5/125	2000 Meters	275 Meters	550 Meters	33 Meters	N/A	
OM2	50/125		550 Meters		82 Meters		
OM3*					300 Meters	100 Meters	100 Meters
OM4*					400 Meters	150 Meters	150 Meters
Singlemode							
OS1	9/125	2000 Meters	5 km at 1310nm	5 km at 1310nm	10 km at 1310nm		
* Laser Optimised							

WARRANTY

3-years limited warranty

