

4Cabling Pty Ltd ABN 74 123 035 889 4cabling.com.au

SALES SUPPORT: 1300 855 235 sales@4cabling.com.au

STORE LOCATIONS: Sydney | Melbourne | Brisbane | Perth



# 4C | Angle Extension Socket IP66 500V 4Pin 20A

#### **Product Images**







## 4C | Angle Extension Socket IP66 500V 4Pin 20A

The 4Cabling Industrial Extension Socket Series are IP66-certified, suitable for outdoor, industrial and commercial use, and available in a choice of pin and voltage.

### **FEATURES**

- Available in 10A-32A Options
- Suitable for medium to large single-phase and three-phase loads.
- Locking rings to ensure IP66 rating.
- Better and safe cable entry
- Polycarbonate housing with premium resins to withstand extreme weather conditions
- Small and large cable seals provided to suit a wide range of cable dimensions.
- Quick assembly with a screwed ring for securing to socket outlets and to ensure IP66 rating
- Impact-resistant, UV stabilised mouldings with high-quality resins
- Transparent pin surround provides quick and sure location of plug-in socket and protection of pins
- Stronger cord clamp and body sleeve connection
- Wider lock-ring is easier to unscrew from sockets (ideal for operating while wearing protective gloves)
- · Premium grade stainless steel and brass internal mechanisms ensure reliable operation in harsh conditions
- Plugs feature locking rings to ensure they do not fall out and to maintain IP ratings.

#### **SPECIFICATIONS**

QUANTITY IN PACK

COLOUR Orange
PIN CONFIGURATION 4 Round
MATERIAL Polycarbonate
SUPPLY VOLTAGE 500V 20A
NOMINAL CONDUCTOR SIZE2.5mm²
MAX CABLE DIAMETER 14,4mm

**COMPLIANCES** AS 60529:2004/NZS IEC 60947.1:2015 AS/NZS 3121:2002 AS/NZS 3100:2017 A1

WARRANTY 3 Years

### WHY 4CABLING?

- 100% Aussie Owned and Operated
- Expert Advice and Sales Team
- Trusted by Over 100,000 Aussie Customers
- ISO 9001, NSW & QLD Government Approved Supplier
- Massive Stock Levels, Ready to Go
- Lightning Fast Delivery Nationwide
- Warranty & Easy Return Policy
- Secure Online Shopping 24/7

