



LC SM M to F/M Attenuator 10dB

Product Images



Description

LC SM M to F/M Attenuator 10dB

Our LC fiber optic attenuators can provide a stable attenuation from 1 to 20dB at both 1310nm and 1550nm transmission windows. The plug type of this attenuator is male-to-female. Our LC fiber optic attenuator features excellent performance and is compliant with IEC 60869-1 and is fully compatible with all LC/UPC connectors and adaptors.

Specifications:

- Characteristics : Single-mode (9/125µm)
- Operating Wavelength : 860, 1310nm, 1550nm
- Return loss (UPC) : $\geq 55\text{dB}$
- Attenuation Accuracy : $\pm 0.75\text{dB}$
- Operating Temperature : $-20 - +75^{\circ}\text{C}$
- Storage Temperature : $-40 - +75^{\circ}\text{C}$
- Mating Durability : ≥ 1000 cycle
- Body Dimension(mm) L x W x H : 28.65 x 6.3 x 10.5

Compliances and Standards:

The performance of the attenuator has been carefully designed to meet the toughest Telcordia standards

- GR-326-CORE
- RoHS-Compliance of item and package
- Performance according to IEC

WARRANTY

1-year limited warranty

WHY 4CABLING?

- Australia's leading importer & wholesaler of 19" server racks, copper, ethernet cable, fibre optic leads & structured networking products
- ISO 9001, NSW Govt. & GITC (QLD Govt.) approved supplier
- Secure online shopping 24/7
- A loyal customer base of 100k+ who trust us for their data & electrical needs
- Over 3000 quality products in stock ready to go
- All products are approved as per local Australian standards
- Warranty & peace of mind return policy
- Lightning fast delivery nationwide
- Expert advice
- Proudly 100% Australian owned & operated

