



## Arista compatible ( QSFP-100G-SRBD )100G BiDI QSFP28 850nm up to 100M for MMF with LC connectors and DOM | BIQSFP28-SR-ARI

### Product Images

---



### Description

---

**Arista compatible ( QSFP-100G-SRBD )100G BiDI QSFP28 850nm up to 100M for MMF with LC connectors and DOM**

# | BIQSFP28-SR-ARI

This product can support 100Gb/s bit rates. It is Parallel Quad Small Form-factor Pluggable (QSFP28) Bi-Directional optical module. The module integrates four optical electrical data into two optical lanes (by Dual Wavelength VCSEL Bi-Directional Optical Interface, 850nm, and +900nm) to allow optical communication over a 2-fibre duplex LC optical multi-mode fibre. Reversely, on the receiver side, the module de-multiplexes 2 sets of optical input signals and converts them to 4 channels of electrical data.

An optical fibre ribbon cable with LC connector can be plugged into the QSFP28 module receptacle. Proper alignment is ensured by the guide pins inside the receptacle. The cable usually cannot be twisted for proper channel-to-channel alignment. An electrical connection is achieved through an MSA-compliant 38-pin edge-type connector.

The module operates by a single +3.3V power supply, LVCMOS/LVTTL global control signals, such as Module Present, Reset, Interrupt, and Low Power Mode, are available with the modules. A 2-wire serial interface is available to send and receive more complex control signals, and to receive digital diagnostic information. Individual channels can be addressed and unused channels can be shut down for maximum design flexibility,

The product is designed with form factor, optical/electrical connection, and digital diagnostic interface according to the QSFP28 Multi-Source Agreement (MSA). It has been designed to meet the harshest external operating conditions including temperature, humidity, and EMI. The Module offers very high functionality and feature integration, accessible via a two-wire serial interface.

## FEATURES

- QSFP28 MSA Compliant
- Supports 100GE Aggregated bit rates
- Supports KP4 FEC @ 100G data rate
- Two independent full-duplex channels
- Up to 100m OM4 MMF transmission
- Single 3.3V power supply
- Maximum power consumption 4w
- LC optical connector
- RoHS-6 compliant
- Case operating temperature 0°C to +70°C

## APPLICATIONS

- Data Center Interconnect
- 100G Ethernet
- Infiniband HDR

## WARRANTY

1 - year limited warranty

## WHY 4CABLING?

- Australia's leading importer & wholesaler of 19" server racks, copper, ethernet cable, fibre optic leads & structured networking products
- ISO 9001, NSW Govt. & GITC (QLD Govt.) approved supplier
- Secure online shopping 24/7
- A loyal customer base of 100k+ who trust us for their data & electrical needs
- Over 3000 quality products in stock ready to go
- All products are approved as per local Australian standards
- Warranty & peace of mind return policy
- Lightning fast delivery nationwide
- Expert advice
- Proudly 100% Australian owned & operated

