



Teltonika | TSW010 | 5 Port Industrial DIN Rail Unmanaged Ethernet Switch, Plug-N-Play

Product Images



Teltonika | TSW010 | 5 Port Industrial DIN Rail Unmanaged Ethernet Switch

DIN Rail Switch

The TSW010 offers the most affordable way to extend network connectivity to multiple Ethernet devices. Five 10/100 Mbps Ethernet ports ensure stable and reliable connectivity, sufficient for most industrial applications where high throughput is not required.

FEATURES

- **Plug and Play:** No additional configuration is needed
- **Mounting:** Integrated DIN rail bracket and surface mounting options
- **Industrial Design:** Anodized aluminum housing and panels
- **Ethernet:** 5 x Ethernet ports with speeds of up to 1000 Mbps

SPECIFICATIONS

- **Bandwidth (Non-blocking):** 1 Gbps
- **MAC address table size:** 2K entries
- **Jumbo frame support:** Store-and-Forward
- **Connector:** 2-pin industrial DC power socket
- **Input voltage range:** 9 - 30 VDC
- **PoE (passive):** Passive PoE. Possibility to power up through the first LAN port, not compatible with IEEE802.3af, 802.3at and 802.3bt standards
- **Power Consumption:** Idle: 0.3 W / Max: 0.9 W
- **Ethernet:** 5 x RJ45 ports, 10/100 Mbps
- **Dimensions:** 113.1W x 27.4H x 80.5D mm
- **Weight:** 146.5 g
- **Mounting options:** Integrated DIN rail bracket, wall mounting (additional kit needed), flat surface placement
- **Operating temperature:** -40 °C to 75 °C
- **Operating humidity:** 10 % to 90 % non-condensing
- **Ingress Protection Rating:** IP30
- **Regulatory:** CE, REACH, RoHS, WEEE UKCA, FCC, IC, CB, RCM
- **Standards:** EN IEC 62368-1:2020+A11:2020

CONTENTS

- TSW010
- QSG (Quick Start Guide)

ACCESSORIES (Not included)

- Power Supply Unit:
 - [TT.PR3PRAU6 | AU 2-Pin Power Supply 9W](#)
 - [TT.PR3PDNP0 | DIN Rail Power Supply Unit 20W](#)
- Mounting Options:
 - [TT.PR5MEC12 | Surface mounting KIT](#)

WARRANTY

2-years limited warranty

