



Teltonika | PR3PRAU6 | 2 Pin AU Power Supply Unit 9W

Product Images



Description

Teltonika | PR3PRAU6 | 2 Pin AU Power Supply Unit 9W | Suitable for TRB2xx, TSW010, TSW114, TSW210, TSW304

The PR3PRAU6 is designed to be used with [TRB245AU](#), [TRB255](#), [TSW010](#), [TSW114](#), [TSW210](#), [TSW304](#).

SPECIFICATIONS

- **Input voltage:** 100 – 240 VAC
- **Input frequency:** 50 / 60 Hz

- **Input current:** 0.45 A
- **Input connector:** AU (Type I)
- **Output voltage:** 9 VDC
- **Output current:** 1.0 A
- **Output connector:** 2-pin, with cord end terminals
- **Weight:** 81g
- **Input voltage range:** 90 – 264 VAC
- **Input frequency range:** 47 – 63 Hz
- **Maximum input inrush current:** 60 A
- **Output voltage maximum deviation:** 8.55 – 9.45 VDC
- **Short circuit protection:** Yes
- **HIPOT (dielectric withstand test):** Primary to Secondary: 4000 VDC
- **MTBF:** 30000 h
- **PSU efficiency standard:** DoE Level VI
- **Certification:** Safety: AS/NZS 62368.1:2018, AS/NZS 3112:2017, EMC: EN 55032:2015

WARRANTY

2-years limited warranty

