



TP-Link | TL-SX3206HPP | JetStream 4 Port 10GBase-T and 2 Port 10GE SFP+ L2+ Managed Rackmount Switch with 4 Port PoE++

Product Images



TP-Link | TL-SX3206HPP | JetStream 4 Port 10GBase-T and 2 Port 10GE SFP+ L2+ Managed Rackmount Switch with 4 Port PoE++

The TP-Link TL-SX3206HPP JetStream Managed Switch is an ultimate networking solution designed to transform your network infrastructure. This switch offers lightning-fast connectivity with 4× 10 Gbps RJ45 ports and 2× 10 Gbps SFP+ slots, delivering a blazing-fast 10G connection for seamless data transfer and enhanced productivity.

With four 802.3af/at/bt PoE++ 10G ports, each capable of delivering up to 60W of power, this switch is ideal for deploying Omada Wi-Fi 6 Access Points, ensuring your devices remain connected and powered. Additionally, it provides advanced L2 and L2+ features, including Static Routing, enterprise-level Quality of Service (QoS), and IGMP Snooping, enabling you to optimize your network for efficiency and security.

The TL-SX3206HPP places a strong emphasis on security, offering robust strategies to safeguard your network from threats and unauthorized access, ensuring the security of your valuable data. Moreover, the switch provides seamless network management options, including web-based management, CLI (Console Port, Telnet, SSH), SNMP, RMON, and Dual Image support, while also integrating into Omada SDN for centralized cloud management and remote access.

Upgrade your network today with the TL-SX3206HPP to enjoy lightning-fast 10G connectivity, harness the power of 802.3bt PoE++, and embrace centralized cloud management. Elevate your network's performance and security, and don't miss out on this powerful networking solution. Order now and experience the transformative difference it can make in your network infrastructure.

FEATURES

- **Full 10G Lightning-Fast Connection:** Offers high-bandwidth connectivity with lightning-fast 4× 10 Gbps RJ45 ports and 2× 10 Gbps SFP+ slots
- **PoE++ Output with 200 W Power Budget†:** Four 802.3af/at/bt PoE++ 10G ports with up to 60 W PoE output on each port make it ideal for the deployment of Omada Wi-Fi 6 APs.‡
- **Abundant L2 and L2+ Features:** Supports a complete lineup of L2 and L2+ features, including Static Routing, enterprise-level QoS, and IGMP Snooping
- **Robust Security Strategies:** Supports a complete lineup of L2 and L2+ features, including Static Routing, enterprise-level QoS, and IGMP Snooping
- **Static Routing:** Helps route internal traffic for more efficient use of network resources
- **Centralised Cloud Management:** Integrates into Omada SDN for cloud access and remote management
- **Standalone Management:** Web, CLI (Console Port, Telnet, SSH), SNMP, RMON, and Dual Image bring powerful management capabilities

†PoE budget calculations are based on laboratory testing. The actual PoE power budget is not guaranteed and will vary due to client limitations and environmental factors. The maximum power output of every single PoE++ port is 60 W.

‡TL-SX3206HPP is incompatible with Passive PoE and other non-standard PoE devices. The standards refer to IEEE 802.3af/at/bt.

WARRANTY

3-year limited warranty

