



Teltonika | PR3P2AU3 | 2 Pin AU Power Supply Unit 24W

Product Images



Description

Teltonika | PR3P2AU3 | 2 Pin AU Power Supply Unit 24W | Suitable for RUTX12, RUTX14

The PR3P2AU3 is designed to be used with the [RUTX12](#) and [RUTX14](#). It has an AU plug and support input voltage from 100 VAC to 240VAC.

SPECIFICATIONS

- **Input voltage:** 100 - 240 VAC
- **Input frequency:** 50/60 Hz
- **Input current:** 0.8 A
- **Input connector:** AU (Type I)

- **Output voltage:** 12 VDC
- **Output current:** 2.0 A
- **Output connector:** 4-pin, 3 mm pitch
- **Weight:** 115 g
- **Input voltage range:** 90 – 264 VAC
- **Input frequency range:** 47 – 63 Hz
- **Maximum input inrush current:** 60 A
- **Output voltage maximum deviation:** 11.4 – 12.6 VDC
- **Short circuit protection:** ✓
- **HIPOT (dielectric withstand test):** Primary to Secondary: 4000 VDC
- **MTBF:** 30000 h
- **PSU efficiency standard:** DoE Level VI
- **Certification:**
Safety: AS/NZS 60950.1:2015, AS/NZS 60065:2012 Inc A1

EMC: AS/NZS CISPR 22:2009+A1:2010, AS/NZS CISPR 13:2012, EN 55032:2012, EN 55024:2010, EN 55020:2007+A11, EN 61000-3-2:2014, EN 61000-3-3:2013

WARRANTY

2-years limited warranty

