

## Mean Well | NDR-480-24 | 24V DIN Rail Power Supply 20A 480W

#### **Product Images**



# Mean Well | NDR-480-24 | 24V DIN Rail Power Supply 20A 480W

NDR-480 is one economical slim 480W DIN rail power supply series, adapt to be installed on TS-35/7.5 or TS-35/15 mounting rails. The body is designed 85.5mm in width, which allows space saving inside the cabinets. The entire series adopts the full range AC input from 90VAC to 264VAC and conforms to BS EN/EN61000-3-2, the norm the European Union regulates for harmonic current.

NDR-480 is designed with a metal housing that enhances the unit's power dissipation. With working efficiency up to 92.5%, the entire series can operate at the ambient temperature between -20°C and 70°C under air convection. It is equipped with constant current mode for over-load protection, fitting various inductive or capacitive applications. The complete protection functions and relevant certificates for industrial control apparatus (UL508, TUV BS EN/EN62368-1 etc) make NDR-480 a very competitive power supply solution for industrial applications.

#### **FEATURES**

- Universal AC input/ Full range
- Built-in active PFC function
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- UL 508 (industrial Control equipment) approved
- BS EN/EN61000-6-2(BS EN/EN50082-2) industrial immunity level
- 100% full load burn-in test

### **SPECIFICATIONS**

- Output Voltage: 24V
- Protections: Short circuit/ Overload/Over Voltage/ Over temperature

#### **APPLICATIONS**

- Industrial control system
- Factory automation
- Electro-mechanical apparatus

#### WARRANTY

3-years limited warranty

