

4Cabling Pty Ltd ABN 74 123 035 889 4cabling.com.au SALES SUPPORT: 1300 855 235 sales@4cabling.com.au STORE LOCATIONS: Sydney | Melbourne | Brisbane | Perth



3m ST-ST OS1 Singlemode Fibre Optic Cable: Yellow

Product Images





Description

#m ST-ST OS1 Singlemode Fibre Optic Cable: Yellow - 2mm Oversleeving

Fibre patch cables are the thin, flexible fibres of glass that carry data, telephone conversations and emails high speed all over the world in a matter of seconds with much less interference than copper patch lead. Fibre Optic cables need less amplification to boost signals so they travel better over longer distances.

4Cabling 's OS1 / OS2 singlemode fibre optic patch leads provide the connection from Ethernet 10Mbit/s to 10Gbit/s Gigabit Ethernet, they are the cost-effective way to replace your copper-based patch leads. 4Cabling fibre optic cable is immune to EMI/ RFI frequency, mainly used on patch panels for the connection between outlets and terminal equipment. The singlemode optical fibre cables are manufactured using LSZH cables which conform to IEC, EIA TIA and Telcordia standards.

4Cabling Singlemode Fibre Optics leads is the cost-effective way of your cabling solution.

2mm OVERSLEEVING. WARRANTY 3 YEARS. UPC (Ultra Physical Contact) Connector

Application:

- Cross-connect patching
- Backbone application in building
- Termination enclosure for equipment patching
- Equipment to equipment patching

Features:

- Conforms to ISO/ IEC 11801
- Individually labelled for lead tracing
- Low smoke zero halogen (LSZH) cable
- Manufactured with stringent quality control
- UPC (Ultra Physical Contact) connector
- All leads are supplied with a factory test report
- OS2 fibre patch leads conform to ITU-T G.652.D, TIA/EIA 492CAAB
- Duplex configurable assemblies for LC, SC, ST & SC/A, as well as MTRJ Patch leads
- All ends are polished and individually inspected for correct polishing
- Supports high-speed multi-channel data, voice & video applications

FIBRE SPECIFICATIONS

Mode: OS1 / OS2 SinglemodeFibre Terminations: ST-ST

Length: 3mColour: YellowOversleeving: 2mm

| Multimode | Core/Cladding Diameter (µm) | Fast Ethernet 100BASEFX | 1 Gigabit 1000BASE-SX | 1 Gigabit 1000BASE-LX | 10 Gigabit 10GBASE | 40 Gigabit 40GBASE | 100 Glgabit 100GBASE |
|-------------------|--------------------------------|----------------------------|--------------------------|--------------------------|-----------------------|-----------------------|-------------------------|
| OM1 | 62.5/125 | 2000 Meters | 275 Meters | 550 Meters | 33 Meters | N/A | |
| OM2 | | | 550 Meters | | 82 Meters | | |
| OM3* | 50/125 | | | | 300 Meters | 100 Meters | 100 Meters |
| OM4* | | | | | 400 Meters | 150 Meters | 150 Meters |
| Singlemode | | | | | | | |
| OS1 | 9/125 | 2000 Meters | 5 km at 1310nm | 5 km at 1310nm | 10 km at 1310nm | | |
| * Laser Optimised | | | | | | | |

WARRANTY

3 year limited warranty.

