



Teltonika | TAP200 | Wave-2 802.11b/g/n/ac Dual Band Wi-Fi 5 Access Point

Product Images



Description

Teltonika | TAP200 | Wave-2 802.11b/g/n/ac Dual Band Wi-Fi 5 Access Point

Upgrade your network infrastructure with the Teltonika TAP200 Wave-2 802.11b/g/n/ac Dual Band Wi-Fi 5 Access Point. With dual-band technology and fast roaming capabilities, this access point delivers high-performance Wi-Fi coverage in medium-density spaces. Its sleek design and integrated mounting bracket ensure easy installation, blending seamlessly into any environment. Plus, with PoE-in functionality, it's both versatile and efficient.

With its robust features and reliable performance, the Teltonika TAP200 Access Point is an ideal solution for upgrading your Wi-Fi network.

FEATURES

- **WI-FI 5:** Wave-2 802.11 b/g/n/ac Dual Band Wi-Fi
- **RJ45 & POE-IN:** Supporting speeds of up to 1000Mbps and PoE-in functionality
- **Resilient & Easy to Install:** UV-stabilised housing for lasting colour with a mounting bracket for quick setup
- **RMS Management:** Free RMS Management access for 24 months

SPECIFICATIONS

- **Dimensions (W x H x D):** Ø 158mm x 30mm
- **Colour:** White
- **Weight:** 190g
- **Casing Material:** UV stabilized plastic casing
- **Mounting Options:** AP Mounting Bracket (for ceiling mount)
- **Wireless Mode:** 802.11b/g/n/ac Wave 2 with data rates up to 867Mbps
- **Wi-Fi Security:** WPA2-EAP/WPA3-EAP, WPA3-SAE, AES-CCMP, TKIP, and more
- **Ethernet:** 1 x RJ45 10/100/1000Mbps port
- **CPU:** MediaTek Dual-Core 880MHz MIPS 1004Kc
- **RAM:** 256MB DDR3
- **Flash Storage:** 16MB SPI NOR Flash
- **Power:** PoE standards 802.3af PoE Class 1, input voltage range 44.0 – 57.0V
- **Physical Interfaces:** 1 x RJ45 port, 2 x internal antennas for both 2.4GHz and 5GHz Wi-Fi
- **Operating Environment:** Temperature range -40 °C to 75 °C, IP30 rating for protection against dust and moisture
- **Regulatory Approvals:** CE, UKCA, FCC, IC, RCM, CB, EAC, UCRF, WEEE

WARRANTY

2-years limited warranty

