

OE Elsafe | QIKPAC 600454 | Commercial Grade Power Bank | 3 Battery Pack with Charging Base | WHITE

Product Images







Description

OE Elsafe | QIKPAC 600454 | Commercial Grade Power Bank | 3 Battery Pack with Charging Base and TUF-R® HP A+C | WHITE

*** IMAGE SHOWN IS OF THE QIKPAC 60045 | BLACK ***

Introducing the OE Elsafe QIKPAC 600454, a powerhouse of portable energy designed for the demands of office environments.

This commercial-grade power bank features three high-quality lithium-ion battery packs encased within a robust fire-retardant polycarbonate white body. Also available in black (QIKPAC 600453), it seamlessly integrates into any workspace, ensuring power accessibility wherever you need it.

With its efficient charging capabilities, durable construction, and commitment to safety and sustainability, the OE Elsafe QIKPAC 600454 is the ultimate solution for powering your office devices reliably and responsibly. Say goodbye to downtime and hello to uninterrupted productivity with the QIKPAC by your side.

FEATURES

- Portable 240Wh lithium-ion battery pack
- Premium Lithium-Ion cells for long-lasting performance
- High strength fire retardant polycarbonate construction
- Wieland GST08 50V 6A DC power in and out connectors
- Triple charging base for simultaneous charging of up to three units
- Shipped in UN38.3 certified dangerous goods packaging
- 95% recyclable for environmentally conscious disposal
- ISO9001 quality controlled manufacturing and testing
- Charging times: 5-8 hours for 1-2 batteries and 8-11 hours for 3 batteries

SPECIFICATIONS

• Model: QIKPAC 600454

Colour: WhiteQty in Pack: 3Weight: 4.331kg

• **USB Charging Outlets**: 1 x Type A Female, 1 x Type C Female

Input Connection: 1x GST08 Male
 Output Voltages and Currents:

- Type C: MAX 60W 20V/3A, 15V/3A, 9V/3A, 5V/3A (PD3.0), QC 2/3.0 5V/3A, 9V/2A, 12V/1.5A
- Type A: MAX 12W 5V/2.4A IDR BC1.2, Apple 12W Mode, Samsung Fast Charge

Rated Total Output Power: 72W MAX
 Operating Temperature: 0°C to 25°C

• LED Indicator: Digital control with auto reset and power status indicators

• Safety Standards: IEC 62368-1:2018 (safety), EN61204:2018 (EMC)

TUF-RHP A+C

FEATURES

- High strength fire retardant polycarbonate construction
- Comes with GST08 cable for power connection
- Quality tested with ISO9001 standards
- CE marking compliant with EMC, Low Voltage Equipment, and ROHS3 Directives
- USB charger with Type A Female and Type C Female outlets
- Extractable GST08 cable from QF05 TUF-R HP body
- Over Current, Short Circuit, and Over Temperature protection
- LED indicator for power status

SPECIFICATIONS

- Colour: White
- USB Charging Outlets: 1 x Type A Female 1 x Type C Female

- Input Connection: 1x GST08 Male
 Output Voltages and Currents:
 - Type C: MAX 60W 20V/3A, 15V/3A, 9V/3A, 5V/3A (PD3.0), QC 2/3.0 5V/3A, 9V/2A, 12V/1.5A
 - o Type A: MAX 12W 5V / 2.4A IDR BC1.2, Apple 12W Mode, Samsung Fast Charge
- Input Voltage: 24-30V DC
- Rated Total Output Power: 72W MAX
- USB Connector: Min. Insertions: 10,000 for Type A, 10,000 for Type C
- Operating Temperature: 0°C to 25°C
- Standards: IEC 62368-1:2018 (safety), EN61204:2018 (EMC)

COMPRISING

- 3 x QIKPAC Carry TUF HP WHITE
- 1 x QIKPAC Charger Base Triple WHITE
- 1 x 2000mm 10A Cable 3 Pin Plug White- Thermal Overload

WARRANTY

1-year limited warranty

