![4Cabling logo] Quality Products for a Connected World.

4Cabling Pty Ltd
ABN 74 123 035 889
4cabling.com.au

SALES SUPPORT:
1300 855 235
sales@4cabling.com.au

STORE LOCATIONS:
Sydney | Melbourne |
Brisbane | Perth

Socomec | NET-VISION8-EMD | NETVISION ENVIRONMENT SENSOR

Product Images

Description

Socomec NET-VISION8-EMD | Environment Monitoring Sensor

Introducing the Socomec NET-VISION8-EMD, the ultimate environmental monitoring sensor designed to seamlessly integrate with Netys PR and ITYS systems. Engineered for precise monitoring of temperature and humidity, this state-of-the-art sensor ensures optimal environmental conditions for your critical equipment. With the ability to connect directly to the NET-VISION8CARD (SNMP card), the NET-VISION8-EMD offers real-time data and alerts, making it indispensable for maintaining your IT infrastructure's health and reliability.

The NET-VISION8-EMD is perfect for businesses requiring meticulous environmental oversight. Whether you're managing a data center or a server room, this sensor provides actionable insights through email or SNMP traps if the monitored values exceed user-defined thresholds. Additionally, it features four digital inputs from dry contacts, allowing for comprehensive monitoring and instant alarm triggers, safeguarding your operations against potential disruptions.

FEATURES

- Connects to Net Vision systems for real-time environmental monitoring
- Monitors ambient temperature and humidity accurately
- Includes four digital inputs from dry contacts for versatile monitoring

- Provides email or SNMP trap alerts if values exceed user-defined thresholds
- Triggers alarms if input contacts are closed or open, ensuring prompt response
- Integrates with NET VISION for server shutdown conditions based on EMD events
- User-configurable DIP code for customized setup

SPECIFICATIONS

- **Compatibility:** Netys PR & ITYS (not compatible with previous versions NET VISION 7 & 6)
- **Network Address:** 192.168.1.2
- **Ambient Temperature Range:** User-specified, current reading 30.5°C
- **Humidity Range:** User-specified, current reading 12%
- **Digital Inputs:** 4 inputs from dry contacts
- **Alerts:** Email or SNMP traps
- **Alarm Triggers:** Based on input contact status
- **DIP Code:** User configurable
- **Connection Requirement:** Must connect to NET-VISION8CARD (SNMP card)

WARRANTY

1-year limited warranty