



TP-Link TL-SF1016: 16-port Unmanaged 10/100M Rackmount Ethernet Switch

Product Images



TP-Link TL-SF1016: 16-port Unmanaged 10/100M Rackmount Ethernet Switch

This 16-Port Fast Ethernet Switch TL-SF1016 is designed to meet the needs of the most demanding workgroup and departmental connectivity requirements. A reliable, easy-to-use switch without the complexity of management, this switch provides 16 10/100Mbps ports.

- > **16 10/100Mbps RJ45 ports**
- > **Innovative energy-efficient technology** saves power up to 40%
- > **Supports MAC address** self-learning and auto MDI/MDIX
- > **Standard 19-inch rack-mountable steel case**
- > **100% Data filtering rate** eliminates all error packets
- > **Supports** IEEE 802.3x flow control for Full Duplex mode and back pressure for Half Duplex mode
- > **Non-blocking switching architecture** forwards and filters packets at full wire-speed for maximum throughput
- > **3.2Gbps Switching Capacity**
- > **Auto-MDI/MDIX** eliminates the need for crossover cables
- > **Supports** MAC address auto-learning and auto-aging
- > **Support** the port N-Way Auto-Negotiation, Store and Forward
- > **Compact size** design for desktops, Rackmountable
- > **Plug and Play** design simplifies installation

Specifications

Hardware Features

Interface: 16 10/100Mbps RJ45 Ports; AUTO Negotiation/AUTO MDI/MDIX

External Power Supply: 100-240VAC, 50/60Hz

Dimensions: 440x180x44 mm

Software Features

Transfer Method: Store and Forward

MAC Address Table: 8K

Advanced Functions: 802.3X Flow Control, Back Pressure; Auto-Uplink Every Port

Others

Certification: FCC, CE, RoHS

System Requirements: Microsoft Windows 98SE, NT, 2000, XP, Vista; or Windows 7, MAC OS, NetWare, UNIX or Linux.

Operating Temperature: 0 to 40 Degrees Celsius

Storage Temperature: -40 to 70 Degrees Celsius

Operating Humidity: 10% to 90% non-condensing

Storage Humidity: 5% to 90% non-condensing

Warranty

- 3-Year Manufacturer 's Warranty

