



OE Elsafe: QIKFIT Twin USB Fast Charger TUF - White

Product Images



Description

OE Elsafe: QIKFIT Twin USB Fast Charger TUF - White

The OE Elsafe QIKFIT 'Twin USB Fast charger TUF' has been developed to provide a compact power source for charging portable devices without the need for plug-in chargers. Simply plug the device's USB charging lead into either the Type-C or Type-A USB port for class-leading charging performance. The QIKFIT Twin USB Fast charger is designed to be used in the OE Elsafe floor, desk, and ceiling boxes.

Developed for full cross-product capability the OE Elsafe QIKFIT Twin USB Fast charger (QIKFIT TUF charger) automatically communicates with the portable device connected so that it can then draw the optimum charging power. Able to fast charge one or two devices simultaneously at up to 6 x faster than a standard PC or laptop USB outlet, and comparable to OEM chargers, the QIKFIT TUF charger satisfies the demands of the most power-hungry devices.

****Housing NOT included****

FEATURES

- Charge one or two devices simultaneously at up to 6 x faster than a standard PC or laptop USB outlet
- Independently tested to the latest Australian safety standards
- Protects against both input and output current overload and short circuits
- Automatically communicates with the portable device connected
- Sleek modern design
- All sockets are auto switched
- The soft-wired QIKFIT do not use regular IEC Connectors as they come with GST male and female connectors allowing for multiple QIKFITS to be daisy-chained. You will need to use this with an [OE-Elsafe starter](#) and/or [interconnecting cable](#)
- Designed to easily clip onto an [OE Elsafe Prodigy Basket](#) and QIKFIT-compatible boxes and modules

SPECIFICATIONS

- Material: Polycarbonate Body
- Colour: White
- Dimensions: 185.5mm x 41.5mm x 24mm
- USB Charging Outlets: 1 x Type-C & 1 x Type-A
- Charging current: Max 5A in total
- AC voltage range: 200-240VAC at 50/60Hz
- AC input current: Max 0.6A at full load, less than 0.5mA at no load
- Rated total output: 25W
- Output voltage: 5V DC +/- 5%
- Standby power use: Less than 0.1W
- Life expectancy: Min. 5 years in normal use
- USB Connectors: Gold Plated for Improved Contact Type-A specifically manufactured for a minimum of 5000 insertions. Type-C for a minimum of 10,000 insertions
- Over current protection: Self Limiting
- Short circuit protection: Self Resetting
- Compatibility: Apple iPad/iPhone, Android, Samsung, Blackberry
- Operating temperature range: 0° to 35°C
- Max relative humidity: 85% RH

WARRANTY

1-year limited warranty

WHY 4CABLING?

- Australia's leading importer & wholesaler of 19" server racks, copper, ethernet cable, fibre optic leads & structured networking products
- ISO 9001, NSW Govt. & GITC (QLD Govt.) approved supplier
- Secure online shopping 24/7
- A loyal customer base of 100k+ who trust us for their data & electrical needs
- Over 3000 quality products in stock ready to go
- All products are approved as per local Australian standards
- Warranty & peace of mind return policy
- Lightning fast delivery nationwide
- Expert advice
- Proudly 100% Australian owned & operated

