

15RU CLASSIC SERIES

SPECIFICATIONS

- **Static loading: 90kg**
- **Width: 600mm**
- **Depth: 450mm, 550mm**
- A reversible toughened glass front door
- Powder coated, black coloured
- Generous top and bottom cable entry
- Generous rear entry for cabling
- L shaped vertical uprights adjustable forward and back
- **Material:** SPCC quality cold rolled steel
- **Surface Finish:** Degrease, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting.
- Compatible with 19" International Standard
- Quick release side panels
- RU Markings - front and back
- Vented front and sides for maximum cooling



Front Lock




Swing Gate
(RW-15R-550 only)



RU Markings



2 x Fan System
(Optional)



Fixed Shelf



PDU-H1R-8
(Optional)

2 YEARS WARRANTY

15RU WALL MOUNT CABINETS

Model	W X D X H (mm)	Capacity	Shelf (s)	Fan (s)	PDU	Swing Gate	M3	Weight (kg)
RW-15R-450	600 x 450 x 769	15RU	1	No 2 x Optional	Yes	No	0.242	32
RW-15R-550	600 x 550 x 769	15RU	1	No 2 x Optional	Yes	Yes	0.293	35

FEATURES

- Heavy duty frame work
- 1 shelf included
- Reversible front toughened glass door
- Revolving front and side locks
- Vented front and sides for cooling
- Provision for 2 optional fans
- Pre-punched holes for cabling
- 19" adjustable rails (front and back)
- Black colour with clear front door